



BEKA

GBP 6640BM TB40



Cutout: 580 x 580



Product Features and Key Data

Applications : Sales Room - Residential Areas - Hospital - Commercial Building

Luminaire Type : LED Backlight

Mounting Method : Recessed

Luminaire Optic : Opal diffuser. Highly specular reflector

Connected Load : 40W

Colour Temperature : 4000K

Rated Luminous Flux : 4000 lm

Luminous Efficiency : 100 lm/W

Power Factor : > 0,958

CRI Value : > 80

UGR : < 20 (EN124664-1)

Photo Biological Class : Group 0 - No risk

Luminaire Colour : Ral 9016 Traffic white

Luminaire Body : Luminaire body DKP steel. Electrostatic powder coating

Electrical version : With electronic transformer, switchable.

Connection method : Terminal

Mains frequency : 50/60 Hz

Mains voltage : 220 - 240 V

Led Service (25°) : L80 = 50.000 h

Driver (220 - 240V) : Tridonic, Osram or Gecem

Ceiling Type : AB - Gypsum Ceiling

TB - Modular Ceiling

KB - Clip-in Ceiling

Ingress Protection (IP) rating : IP44

Protection class : I

Impact resistance (IK) : IK02

Hot wire resistance : 650 °C

Ambient temperature : - 20 - 35 °C

Options : 1 - 3 Hours Emergency Kit, Dali Dimmable, Pendant Kit

Accessories :