


# TEBIR

## GCP 1236LT SB40



### Product Features and Key Data

<b>Applications :</b>	Education Area - Universities - Schools - High Schools
<b>Luminaire Type :</b>	LED TI luminaires
<b>Mounting Method :</b>	Surface
<b>Luminaire Optic :</b>	PC diffuser
<b>Connected Load :</b>	36W
<b>Colour Temperature :</b>	4000K
<b>Rated Luminous Flux :</b>	3420 lm
<b>Luminous Efficiency :</b>	95 lm/W
<b>Power Factor :</b>	> 0,914
<b>CRI Value :</b>	> 80
<b>UGR :</b>	< 21 ( EN124664-1 )
<b>Photo Biological Class :</b>	Group 0 - No risk
<b>Luminaire Colour :</b>	White Color
<b>Luminaire Body :</b>	Aluminium body and diffuser.
<b>Electrical version :</b>	With electronic transformer, switchable.
<b>Connection method :</b>	Terminal
<b>Mains frequency :</b>	50/60 Hz
<b>Mains voltage :</b>	220 - 240 V
<b>Led Service ( 25° ) :</b>	L80 = 50.000 h
<b>Driver ( 220 - 240V ) :</b>	Tridonic, Osram, Gecem
<b>Ceiling Type :</b>	AB - Gypsum Ceiling TB - Modular Ceiling KB - Clip-in Ceiling
<b>Ingress Protection (IP) rating :</b>	IP40 or IP44
<b>Protection class :</b>	I
<b>Impact resistance (IK) :</b>	IK08
<b>Hot wire resistance :</b>	650 °C
<b>Ambient temperature :</b>	-35 - 55 °C
<b>Options :</b>	1 - 3 Hours Emergency Kit
<b>Accessories :</b>	